

PF	Product Fiche according to (EU) No 65/2014			
S	Supplier's name or trade mark	PYRAMIS		
M	Model identifier	065033001 ELEGANTO 90		
	Annual Energy Consumption	AEC hood	32.6	kWh/a
	Energy Efficiency Class	EEl class	B	
	Fluid Dynamic Efficiency	FDE hood	24.6	%
	Fluid Dynamic Efficiency class	FDE class	B	
	Light Efficiency	LE hood	42.0	lux/W
	Lighting Efficiency Class	LE class	A	
	Grease Filtering Efficiency	GFE hood	49.5	%
	Grease Filtering Efficiency class	GFE class	F	
	Minimum Air Flow in normal use	Q min	195	m³/h
	Maximum Air Flow in normal use	Q max	455.6	m³/h
	Air Flow at intensive/boost setting	Q boost	/	m³/h
	A-weighted Sound Power Emission at minimum speed	SPE min	42	dB(A) re 1pW
	A-weighted Sound Power Emission at maximum speed	SPE max	60	dB(A) re 1pW
	A-weighted Sound Power Emission at intensive or boost speed	SPE boost	/	dB(A) re 1pW
	Power consumption off mode	Po	0.00	W
	Power consumption in standby mode	Ps	0.00	W

Additional Information according to (EU) No 66/2014				
	Time increase factor	f	1.1	
	Energy Efficiency Index	EEl hood	56.5	%
	Measured air flow rate at best efficiency point	Q bep	277.5	m³/h
	Measured air pressure at best efficiency point	P bep	230	Pa
	Maximum air flow	Q max	455.6	m³/h
	Measured electric power input at best efficiency point	W bep	72.0	W
	Nominal power of the lighting system	WL	2.6	W
	Average illumination of the lighting system on the cooking surface	E middle	108	lux