PF	Product Fiche according to (EU) No 65/2014				
S	Supplier's name or trade mark  Model identifier  Annual Energy Consumption	PYRAMIS 065033101 ELEGANTO 60			
					AEC hood
			Energy Efficiency Class	EEI class	В
	Fluid Dynamic Efficiency	FDE hood	24.6	%	
	Fluid Dynamic Efficiency class	FDE class	В		
	Light Efficiency	LE hood	42.0	lux/W	
	Lighting Efficiency Class	LE class	Α		
	Grease Filtering Efficiency	GFE hood	49.5	%	
	Grease Filtering Efficiency class	GFE class	F		
	Minimum Air Flow in normal use	Q min	195	m³/h	
	Maximum Air Flow in normal use	Q max	455.6	m³/h	
	Air Flow at intensive/boost setting	Q boost	1	m³/h	
	A-weighted Sound Power Emission at minimum speed	SPE min	42	dB(A) re 1pW	
	A-weighted Sound Power Emission at maximum speed	SPE max	60	dB(A) re 1pW	
	A-weighted Sound Power Emission at intensive or boost speed	SPE boost	1	dB(A) re 1pW	
	Power consumption off mode	Po	0.00	W	
	Power consumption in standby mode	Ps	0.00	W	

Additional Information according to (EU) No 66/2014					
Time increase factor	f	1.1			
Energy Efficiency Index	EEI hood	56.5	%		
Measured air flow rate at best efficiency point	Q bep	277.5	m³/h		
Measured air pressure at best efficiency point	P bep	230	Pa		
Maximum air flow	Q max	455.6	m³/h		
Measured electric power input at best efficiency point	W bep	72.0	W		
Nominal power of the lighting system	WL	2.6	W		
Average illumination of the lighting system on the cooking surface	E middle	108	lux		

3011080001101 K40NI0001 -